



ULTIMATE CONTROL 33-9012

High Performance Formulated Emulsion

April 2010

Formerly Known as NATIONAL 33-9012

TYPE:

High Performance Formulated Emulsion

PHYSICAL PROPERTIES:

Appearance: White, fluid product

Solids: Approx. 57%

Viscosity: Approx. 1500 cps.

pH: Approx. 4.5

Lbs./Gallon: Approx. 9.1

warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

SUGGESTED USES:

High quality, fast setting, water resistant, glued lap adhesive, especially where good "retack" is required. Meets composition requirements of Indirect Food Additives Regulation 21 CFR 175.105 "Adhesives".

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

OPERATING CONDITIONS:

Direct transfer from a glue wheel, rotary stencil, extrusion.

1. Stir thoroughly before using.
2. Ready-for-use viscosity as supplied. May be diluted with water if desired.
3. Wet film soluble in warm water. Dry film soluble in acetone/water.

04/10KJ

PRECAUTIONS:

Protect from temperatures below 40F. Rotate stock using oldest material first. Keep covered to prevent drying out and contamination. Do not mix with other adhesives.

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all**

Henkel Americas

Tel: +1.866.443.6535, Fax: +1.609.409.5699

For the most direct access to local sales and technical support visit: www.henkelna.com/industrial